

# IEC LOCK

## C19 LOACKABLE OUTLET



### Technical Information

#### General Information

- Snap-in mounting from front
- Solder terminal or quick connect from single terminal
- Protection class 1
- Integral plug retention feature

#### Technical Data

**Rating:** 16A/250VAC

**Insulation Resistance:**  
10M $\Omega$  (500VDC, 1 Min.)

**Dielectric Strength:**  
2KV (50Hz 1 Min) to accessible surfaces

**Materials Socket:**  
Black Thermoplastic UL94V-0

#### Approvals

**16 A/250VAC:** ENEC 05, KEMA KEUR

**20 A/250VAC:** UL

#### Standards

IEC/EN 60320-2-2/FUL498

CSA C22.2 No 182.3-M1987

#### Patent

**UK Number:** 2463468B

**EU Number:** EP2321879A


**HK Number:** HK1141901

**Chinese Patent Application No:**  
CN 102150330 A

Other worldwide patents pending

#### Product

- Black & White IEC320 Snap in 1mm or 1.5mm Panel Thickness
- Quick Connector/Solder 6.3 x 0.8mm



Distributed by

**OMEGA FUSIBILI S.p.A.**

Via Edison, 10 - 20057 Assago (MI) - Italia Tel. +39 02 488481 - Fax +39 02 4882522 e-mail: omega@omegafusibili.it